

ELVIAL

FS50

elvial








FACADES

The facades are always fascinating because they represent a constructional and aesthetic challenge. Their large-scale surface must excel in design and simultaneously achieve performance.


ELVIAL

FS50


This flexible solution seamlessly supports advanced architectural design and engineering requirements. It secures the space against the elements of nature while allowing light to function to the benefit of interior design.




FIXED




SPANDREL




INNER ANGLE CORNER




PROJECTED OUT




FINISHINGS




OUTER ANGLE CORNER



MAIN ENTRANCE



ROUNDED ANGLE CORNER



SKYLIGHT WITH PROJECTED OUT

TECHNOLOGY

THERMAL INSULATION

- 1 Use of specially designed gaskets, additional profiles and **Insulation Bars** for high thermal insulation, excellent sealing and impeccable finish
- 2 Glazing options up to **62mm** for exceptional levels of energy saving and sound reduction
- 3 The FS50 system has a **special edition Passive House A***. Suitable for cool, temperate climates (Central European climate zone), which perfectly meets the requirements of passive buildings

ADVANCED SEALING SYSTEM

- 1 **3 Level** drainage system
- 2 Innovative design of **divided gaskets** for ultimate continuity and repeatability in sealing
- 3 Use of a **special sealing accessory** in the mullion connection area




DESIGN FREEDOM

ATTENTION TO DETAILS

- 1 Capability to create large **grids**. [max glazing weight 800kg]
- 2 Capability of **Same Level appearance** inside or shade creation
- 3 Mullion - Transom connection with the application of a **special foam gasket** that on the one hand absorbs the contractions and expansions and on the other hand does not change the internal appearance of the frame
- 4 Atrium constructions with the use of **special components** that ensure perfection of construction and cover architectural needs
- 5 Use of special gaskets for circular constructions (up to 20° per mullion)
- 6 Compatible with all **ELVIAL** opening systems platform

IDENTITY

DESIGN

Mullion and Transom Depth		50		mm
Mullion Height		14	up to	200 mm
Transom Height		6	up to	205 mm
			second level	49 up to 199 mm

PROPERTIES

Max Glass Thickness		62		mm
---------------------	---	-----------	--	----

PERFORMANCE

ENERGY

Construction 4.000 x 3.000 mm	Double glazing, Ug = 1.1 W/m²K with Swisspacer Ultimate	Uw ≥ 1.43 W/m²K
----------------------------------	--	------------------------

COMFORT

Air Permeability	EN 12152	Class AE [750Pa]
Watertightness	EN 12154	Class RE [1.200Pa]
Resistance to Wind Load	EN 13116	design load ± 2.0 kN/m²
		safety load ± 3.0 kN/m²
Sound Reduction	EN 10140-2	43 dB 46.4/24/44.2

elvial

SEE LIFE FROM A DIFFERENT
VIEW THROUGH ELVIAL'S
ALUMINIUM SYSTEMS

DISCOVER OUR INNOVATIVE TECH

ELVIAL I² INSULATION TECHNOLOGY
ELVIAL PRE-ANODIZING 2IN1

**DISCOVER MORE
ARCHITECTURAL SYSTEMS**

ICONIC W77 AI²
ICONIC W77BS AI²
ICONIC W77ST AI²

ESSENCE W67 HI²
ESSENCE W67BS HI²
ESSENCE W67ST HI²

ELVIAL W60BS SI²
ELVIAL W89 PHI²
ELVIAL W92 HI² AW
ELVIAL W59 SI²

ICONIC D77 AI²
ESSENCE D67 HI²

ELVIAL FS50_SG
ESSENCE SD55
ESSENCE CLADDING CL180

ELVIAL 7600
ACOUSTIC LOUVER

elvial.com

While every effort has been made to ensure information accuracy, ELVIAL bears no responsibility for typographic errors or omissions. Photographs may differ from the actual product. This document is subject to change without prior notice.
Copyright © ELVIAL 2024.G.EM.I 014493035000



ELV1TRIFOLDSS50.GR.202307